

# Diesel Powered Generating Sets C25 D6



## Standard Genset Features

Cummins water cooled Diesel engine,  
Oil and fuel filter fitted, water separator,  
Lube-oil drain valve fitted  
Electric starter & Charge alternator 12 v D.C.  
Mechanical governor  
Normal duty air filter  
Single bearing alternator, class H/H , IP23  
Standard voltage 480/277 volts 60 Hz  
Exciter/Voltage reg - Torque Match as std  
PCC0300  
4 pole MCB  
Welded steel base frame with A/V mounting,  
Fork lift pockets in baseframe  
Single skin metal fuel tank  
Tank capacity of min 12 hours operation at  
70% standby load  
Loose 9 dB(A) silencer  
Set mounted starting battery  
Engine & Alternator Munsell Jade Green  
Radiator and Guarding black  
Packing under shrunk plastic film  
Operation & Maintenance manual  
Standard set of labels

## Engine Specification

Cummins 4B3.3G1  
In-line direct injection  
4-cylinder diesel engine.  
Type  
Water cooled, four cycle, naturally aspirated

### Construction

Two valves per cylinder, forged steel  
crankshaft and connecting rods, cast iron  
block.

### Starting

12 volt negative earth. Battery charging  
alternator 45 amp on engine. Cranking  
current 550 amps at 0°C.

### Fuel System

12 volt fail safe actuator. Spin-on paper  
element fuel filters with Stanadyne fuel  
pump injection system with integral  
mechanical governor. Dual flexible fuel lines  
and connectors. Standard fuel water  
separator.

### Filters

Air cleaner with dry element and restriction  
indicator. Spin-on full flow lube oil filter.

### Cooling

50°C radiator as std  
Oil cooler. Drain Tap

## Generator Set Performance

### Voltage Regulation

Maintains voltage output to within  $\pm 1.0\%$ .  
At any power factor between 0.8 and 1.0  
At any variations from No load to Full load.  
At any variations from Cold to Hot.  
At speed droop variations up to 4.5%.

### Frequency Regulation

Isochronous under varying loads from no  
load to 100% full load when electronic  
governor is fitted.

### Random Frequency Variation

Will not exceed  $\pm 0.25\%$  of its mean value for  
constant loads – no load to full load.

### Waveform

Total harmonic distortion open circuit voltage  
waveform in the order of 1.8%. Three-phase  
balanced load in the order of 5.0%.

### Telephone Influence Factor (TIF)

TIF better than 50.

THF to BS 4999 Part 40 better than 2%.

### Alternator Temperature Rise

Class H insulation.

### Radio Interference

In compliance with BS 800 and VDE levels  
G and N.

## Alternator Specification

### Type

Brushless single bearing, revolving field,  
pole, drip proof, screen protected.  
Class H Insulation, IP23 Protection  
IC 01 cooling system.

Fully interconnected damper winding.

AC exciter and rotating rectifier unit.

Epoxy coated stator winding.

Rotor and exciter impregnated with tropical  
grade insulating oil and acid resisting  
polyester resin. Dynamically balanced rotor  
BS 5625 grade 2.5.

Sealed for life bearings.

Layer wound mechanically wedged rotor.

## Generator Set Options

### Mechanical Options

Compliance - CE Certification (Guarding)

### Fuel system options

Low Fuel Level Shutdown

### Exhaust Options

Exhaust Silencer - Industrial (9 dB), In-Line  
Exhaust Silencer - Residential (25 dB), In-Line  
Flexible and fixing kit for Industrial silencer  
Flexible and fixing kit for Residential silencer

### Warranty

Warranty - 5 Year Extended Standby Appl  
Warranty - 2 Year Extended Prime Appl

### Voltage Connections

277/480V, 3 Phase

254/440V, 3 Phase

240/416V, 3 Phase

230/400V, 3 Phase

220/380V, 3 Phase

115/200V, 3 Phase

110/190V, 3 Phase

220-240V, 1 Phase

### Miscellaneous Options

Coolant heater -240/120V

Battery Charger 110-277V, 3A

Electronic Governing

Automatic Transfer Switches

Packing - Export Box

## Compliance Standards

To BS4999/5000 pt 99,

VDE 0530, UTE5100,

NEMA MG1-22, CEMA,

IEC 34, CSA A22.2,

AS1359, BSS 5514,

ISO 3046 and ISO 8528

Model name	kVA		kWe	
	ESP	PRP	ESP	PRP
C25 D6	30.0	27.5	24.0	22.0

## TECHNICAL DATA

<b>Model</b>	C25 D6	<b>Speed</b>	1800 rpm
<b>Set output</b>	380 480 V 60 Hz	<b>Alternator voltage regulation</b>	±1.0%
<b>Prime Rating</b>	22 kW <sub>e</sub> 27.5 kVA	<b>Alternator insulation class</b>	H
<b>Standby Rating</b>	24 kW <sub>e</sub> 30 kVA	<b>Fuel consumption (Prime)</b>	6.7 l/hr
<b>Engine Make</b>	Cummins	<b>Fuel consumption (Standby)</b>	7.1 l/hr
<b>Engine Model</b>	4B3.3G1	<b>Lubrication system oil capacity</b>	7.5 Litres
<b>Cylinders</b>	Four	<b>Base fuel tank capacity – open set</b>	144 Litres
<b>Engine build</b>	In-line	<b>Coolant capacity</b>	7.9 Litres
<b>Standard Governor/Class</b>	Mechanical	<b>Exhaust temp – prime</b>	460°C
<b>Aspiration and cooling</b>	Naturally Aspirated	<b>Exhaust gas flow – prime</b>	99 l/s
<b>Bore and stroke</b>	95mmx115mm	<b>Exhaust gas back pressure max</b>	75 mm Hg
<b>Compression Ratio</b>	18.2:1	<b>Air flow – radiator*</b>	1.74 m <sup>3</sup> /s
<b>Cubic capacity</b>	3.3 Litres	<b>Air intake – engine (Prime)</b>	41 Litre/s
<b>Starting/Min °C</b>	Unaided/–4°C	<b>Minimum air opening to room</b>	0.50 sq m
<b>Battery capacity</b>	70 A/hr	<b>Minimum discharge opening</b>	0.30 sq m
<b>Gross Engine output – Prime</b>	38kW <sub>m</sub>	<b>Pusher fan head (duct allowance)*</b>	10 mm Wg*
<b>Gross Engine output – Standby</b>	42kW <sub>m</sub>	<b>Heat radiated by eng (Prime)</b>	7.2 kW <sub>m</sub>

### PRIME POWER (PRP)

Prime power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO8528-1.

A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation, in accordance with ISO 3046-1.

### STANDBY POWER RATING (ESP)

The Standby Power Rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

In installations served by unreliable utility sources (where outages last longer or occur more frequently), where operation is likely to exceed 200 hours per year, the prime power rating should be applied.


The Standby Power rating is only applicable for emergency and standby applications where the generator set serves as the back up to the normal utility source.

All ratings are based on the following reference conditions:

- Ambient temperature – 27°C

- Altitude above sea level – 150 metres

- Relative humidity – 60%



## Dimensions and Weights

Model	Engine	Length (mm)	Width (mm)	Height (mm)	Set weight wet (Kg)	Set weight dry (Kg)	Enclosed Weight Wet (Kg)
C25 D6	4B3.3G1	1753	930	1256	609	544	887

Specifications may change without notice

### Cummins Power Generation Limited

Manston Park, Columbus Avenue

Manston, Ramsgate

Kent CT12 5BF, UK

Telephone: +44 (0)1843 255000

Fax: +44 (0)1843 255902

Email: [cpg.uk@cummins.com](mailto:cpg.uk@cummins.com)

[www.cumminspower.com](http://www.cumminspower.com)

[www.cummins.com](http://www.cummins.com)

See your distributor for more information.

